

Item Code: TRD EMS Compact Terminal Block for CT

Lead time 7 Days

Item Description:

Compact terminal block; for current and voltage transformers; 6,00 mm²; multicoloured

Contains:

- 8 x 2-conductor disconnect/test terminal block, with touch-proof test sockets, for 4 mm Ø test plugs (2007-8821)
- 4 x 2-conductor disconnect/test terminal block, with touch-proof test sockets, for 4 mm Ø test plugs (2007-8811)
- 1 x 2-conductor ground terminal block, with touch-proof test socket, for 4 mm Ø test plugs (2007-8807)
- 4 x circuit jumper, insulated, 2-way (2007-8442)
- 4 x locking cover, mechanically locks multiple links, 2-pole (282-882)
- 1 x locking cover, mechanically locks multiple links, 4-pole (282-884)
- 2 x end and separator plate, 1.5 mm thick, without lock-out seal option (2007-8892)
- 25 x WMB Inline, plain, 1,500 WMB markers (5 mm) per reel (2009-115)
- 2 x screwless end stop, 10 mm wide (249-117)

Dimensions:

Width	127 mm / 5 inches
Height	99.6 mm / 3.921 inches
Depth from upper-edge of DIN-rail	65.3 mm / 2.571 inches
Module width	8 mm / 0.315 inches
Mounting type	DIN-35 rail
Marking level	Center/side marking
Color	multi-colored
Material group	I
Insulation material (main housing)	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	6.477MJ
Weight	402.4g

Electrical Data:

Nominal voltage (III/3)	500V
Rated impulse voltage (III / 3)	6kV
Legend (ratings)	(III / 3) \triangleq Overvoltage category III / Pollution degree 3

CE Approval:

EN 50155

EN 45545-2